

MT-IK10 IP67

Impact resistant / Waterproof

encapsulite

ILLUMINATING BY DESIGN



H55mm x W57mm



Light output 180°



Linear diffused fluorescent light.

The MT-IK10 IP67 is a slim D shaped lit tubular design that can be surface mounted with stainless steel clamps. This light offers a 180° light distribution through its polycarbonate opal diffuser.

The MT-IK10 IP67 is an incredibly strong linear lighting solution with a wall thickness of 3mm.

55mm High x 57mm wide the MT-IK10 IP67 offers switched or DALI dimming options for a controllable level of light output.



MT-IK10 IP67

Impact resistant / Waterproof

Light source information

Fluorescent/Electronic Ballast 3000k, 4000k and 5000k.

Design

Surface mounted.

IP67 rated as standard.

Installation

Surface mounting with clamps.

Dimming

Non-dimmable as standard.

DALI available. +10° for dimming

Optics

Opal/clear diffuser.

Photometric data available.

Miscellaneous

3hr Emergency with or without DALI monitoring HE only.

If you would like to change something, please ask.

Mounting options



Stainless steel mounting bracket cost option

MT-IK10 IP67 SURFACE

PART NR	LENGTH mm	WATTAGE	LOR	Lm/W	CIRCUIT POWER W	CE	230v 50Hz
Clear cover						T5 G5	Class I
MT-IK10 8w	403-433	8w	90	44.0	11	IP67	F
MT-IK10 14w	660-690	14w	100	62.7	15.9	EEI A	850 GWT
MT-IK10 21w	960-990	21w	100	68.6	23		
MT-IK10 28w	1260-1290	28w	100	70.1	30		
MT-IK10 35w	1560-1590	35w	99	72.0	38		
MT-IK10 21w-LED EC	1000-1030	21w	100	68.6	26.5		
MT-IK10 28w-LED EC	1300-1330	28w	100	70.1	33.5		
Satin cover							
MT-IK10 8w SC	403-433	8w	82	36.2	11		
MT-IK10 14w SC	660-690	14w	92	53.6	15.5		
MT-IK10 21w SC	960-990	21w	91	58.8	23		
MT-IK10 28w SC	1260-1290	28w	97	60.3	30		
MT-IK10 35w SC	1560-1590	35w	91	60.7	38		
MT-IK10 21w SC LED-EC	1000-1030	21w	91	58.8	26.5		
MT-IK10 28w SC LED-EC	1300-1330	28w	97	60.3	33.5		

Weitere Informationen/Optionen unter +49 (0) 2241 844 933
oder per E-Mail info@encapsulite-europe.com