

MT50-LED-F AC

Suspended/Surface

encapsulite

ILLUMINATING BY DESIGN



Tube \varnothing 50mm



Cap \varnothing 55mm



Light output 180°



Polished aluminium as standard.
Black optional.

Tubular diffused LED light, black or polished aluminium end caps.

The MT50-LED F AC is a slim robust LED diffused lit tubular design, this can be suspended horizontally or surface mounted. The svelte tube offers a 180° light distribution through its polycarbonate opal diffuser.

The MT50-LED F AC is an incredibly versatile linear lighting solution. Machined polished aluminium end caps can also be finished in black.

50mm diameter, (55mm \varnothing end caps) the MT50-LED F AC makes use of efficient LED technology offering switched or DALI Dimming options for a controllable level of light output.

Suitable for almost any interior application.



MT50-LED-F AC

Suspended/Surface

Light source information

LED/Electronic Driver 3000k 4000k 5000k other variants to order please enquire.

Design

Can be suspended horizontally or surface mounted.

Polycarbonate opal diffuser with polished/black aluminium end caps.

IP20 rated as standard, IP67 available on request (alternative end caps).

Dimming

Non-dimmable as standard.

DALI DSI available .

Installation

Two suspension points for fully adjustable horizontal suspension.

Surface mounting with discreet fixings.

Installation Instructions available on request.

Optics

Opal diffuser.

Clear diffuser available.

Photometric data available.

Miscellaneous

3hr Emergency with or without DALI monitoring.

If you would like to change something, please ask.

Mounting options



Suspension



Plastic clamp



SS clamp

MT50-LED-F AC SUSPENDED/SURFACE

PART NR	LENGTH mm	LM/W	CIRCUIT POWER W	LUMEN W	CE	230v 50-60 Hz
MT50-LED-F1 AC	595	85.3	12	993	ta 25°C	Class I
MT50-LED-F2 AC	1175	95.5	22	2090		
MT50-LED-F3 AC	1755	99.7	33	3173	IP20	LED
MT50-LED-F4 AC	2335	100.3	43	4193		
					EEL A	850 GWT

Weitere Informationen/Optionen unter +49 (0) 2241 844 933
oder per E-Mail info@encapsulite-europe.com